

SAFETY DATA SHEET

1. Identification

Product identifier	IdeaPaint CREATE CLEAR THAT (part A)
Other means of identification	
Product code	IdeaPaint CREATE CLEAR- THAT (part A)
Recommended use	Dry erase coating.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer/Supplier	IdeaPaint 40 Broad Street Boston, MA 02109
Telephone number	617.714.1050
e-mail	marty@ideapaint.com
Emergency	+1.866.519.4752 (US, Canada, Mexico) +1-760-476-3962 (US, Canada, Mexico) Access Code: 333641

2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 4
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
Environmental hazards	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Combustible liquid. Causes skin irritation. Causes eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe fume/gas/mist/vapors/spray. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. Contaminated work clothing should not be allowed out of the workplace.
Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Collect spillage. In case of fire: Use water spray, dry chemical powder, foam, carbon dioxide for extinction.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Siloxanes and silicones, di-me, methoxy ph polymers with ph silsesquioxanes, methoxy-terminated	68957-04-0	40-70
Epoxy resin, MW <= 700	30583-72-3	10-30
Propylene carbonate	108-32-7	3-8
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	1-5
Dibutyltin di(acetate)	1067-33-0	1-5
Ethanol	64-17-5	0.1-1
Ethylbenzene	100-41-4	0.1-1
Xylene	1330-20-7	0.1-1
Silicon dioxide	7631-86-9	0,3-<1

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothes and rinse skin thoroughly with water for at least 15 minutes. Get medical attention if irritation develops or persists.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if irritation develops or persists.

Ingestion

Have victim rinse mouth thoroughly with water. Do not induce vomiting without advice from poison control center. If ingestion of a large amount does occur, call a poison control center immediately.

Most important symptoms/effects, acute and delayed

Irritation of eyes and mucous membranes. Skin irritation. Sensitization.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Water spray. Dry chemical powder. Foam. Carbon dioxide (CO₂).

Unsuitable extinguishing media

No restrictions known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to heat with water spray and remove container, if no risk is involved.

General fire hazards

Combustible liquid.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Keep away from heat, spark, open flames and other sources of ignition. When using do not smoke. Persons with epoxy allergy should not work with this product. Eating, drinking, and smoking should be prohibited in areas where this material is handled, stored, and processed. Avoid inhalation of vapors and contact with skin, eyes and clothing. Avoid release to the environment. Provide adequate ventilation. In case of inadequate ventilation, use respiratory protection. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not reuse this container. "Empty" containers retain product residue (liquid or vapor) and can be dangerous.

Conditions for safe storage, including any incompatibilities

Keep away from heat, spark, open flames and other sources of ignition. Store in accordance with local, regional, national, and international regulations. Store in tightly closed original container in a dry, cool and well-ventilated place. Protect from direct sunlight. Store away from incompatible materials. Keep away from food, drink and animal feeding stuffs. Do not store in unlabelled containers. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Use appropriate container to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Dibutyltin di(acetate) (CAS 1067-33-0)	PEL	0.1 mg/m ³
Ethanol (CAS 64-17-5)	PEL	1900 mg/m ³ 1000 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m ³ 100 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m ³ 100 ppm

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value
Silicon dioxide (CAS 7631-86-9)	TWA	0.8 mg/m ³ 20 mppcf

US. ACGIH Threshold Limit Values

Components	Type	Value
Dibutyltin di(acetate) (CAS 1067-33-0)	STEL	0.2 mg/m ³
Ethanol (CAS 64-17-5)	TWA STEL	0.1 mg/m ³ 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Dibutyltin di(acetate) (CAS 1067-33-0)	TWA	0.1 mg/m3
Ethanol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
	TWA	125 ppm
	TWA	435 mg/m3
		100 ppm
Silicon dioxide (CAS 7631-86-9)	TWA	6 mg/m3
Xylene (CAS 1330-20-7)	STEL	655 mg/m3
	TWA	150 ppm
	TWA	435 mg/m3
		100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Dibutyltin di(acetate) (CAS 1067-33-0)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Dibutyltin di(acetate) (CAS 1067-33-0)

Skin designation applies.

US - Tennessee OELs: Skin designation

Dibutyltin di(acetate) (CAS 1067-33-0)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Dibutyltin di(acetate) (CAS 1067-33-0)

Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

Dibutyltin di(acetate) (CAS 1067-33-0)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles. Wear face shield if there is risk of splashes.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Butyl rubber gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Other

Wear appropriate chemical resistant clothing to prevent any possibility of skin contact. Wear chemical protective equipment that is specifically recommended by the Personal Protective Equipment manufacturer.

Respiratory protection	In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment. No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Transparent liquid
Physical state	Liquid.
Form	Liquid.
Color	Clear.
Odor	Mild.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	> 220 °F (> 104.44 °C)
Flash point	> 190.0 °F (> 87.8 °C) Closed Cup
Evaporation rate	32 BuAc
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.2 hPa (20°C/68°F)
Vapor density	Not available.
Relative density	9.5 lb/gal
Solubility(ies)	
Solubility (water)	Insoluble in water.
Partition coefficient (n-octanol/water)	No data available.
Auto-ignition temperature	> 572 °F (> 300 °C)
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
VOC (Weight %)	< 25 g/l (wt%)

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials.
Incompatible materials	Water. Acids. Oxidizing material. Strong alkaline.
Hazardous decomposition products	Thermal decomposition of this product can generate carbon monoxide and carbon dioxide. Nitrogen oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Vapors and spray mist may irritate throat and respiratory system and cause coughing.
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.
Ingestion	Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Irritation of eyes and mucous membranes. Sensitization.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
------------	---------	--------------

Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate (CAS 41556-26-7)

Acute

Oral

Rat

2369 - 3920 mg/kg

Skin corrosion/irritation Irritating to skin.

Serious eye damage/eye irritation Irritating to eyes.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity This product is not expected to cause mutagenic or genotoxic effects.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Silicon dioxide (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Preparation contains an epoxy resin, which may cause sensitization and development of allergy.

Further information No other specific acute or chronic health impact noted.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability There are no data on the degradability of this product.

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient n-octanol / water (log Kow)

IdeaPaint CREATE CLEAR THAT (part A)

1.7 QSAR-method, (20 °C)

Dibutyltin di(acetate) (CAS 1067-33-0)

1.27

Mobility in soil The product is insoluble in water.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose in accordance with all applicable regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN number	UN3082
UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Dibutyltin di(acetate))
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	8, 146, 335, IB3, T4, TP1, TP29
Packaging exceptions	155
Packaging non bulk	203
Packaging bulk	241

IATA	
UN number	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Dibutyltin di(acetate))
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG	
UN number	UN3082
UN proper shipping name	Environmentally hazardous substances, liquid, n.o.s. (Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Dibutyltin di(acetate))
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethanol (CAS 64-17-5)	LISTED
Ethylbenzene (CAS 100-41-4)	LISTED
Xylene (CAS 1330-20-7)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	0.1-1
Xylene	1330-20-7	0.1-1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Dibutyltin di(acetate) (CAS 1067-33-0)
Ethanol (CAS 64-17-5)
Ethylbenzene (CAS 100-41-4)
Silicon dioxide (CAS 7631-86-9)
Xylene (CAS 1330-20-7)

US. New Jersey Worker and Community Right-to-Know Act

Ethanol (CAS 64-17-5)
Ethylbenzene (CAS 100-41-4)
Silicon dioxide (CAS 7631-86-9)
Xylene (CAS 1330-20-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethanol (CAS 64-17-5)
Ethylbenzene (CAS 100-41-4)
Silicon dioxide (CAS 7631-86-9)
Xylene (CAS 1330-20-7)

US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4)
Xylene (CAS 1330-20-7)

US. California Proposition 65

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Ethanol (CAS 64-17-5)
Ethylbenzene (CAS 100-41-4)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision


Issue date 20-May-2015

Revision date -

Version # 01

Further information The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

NFPA ratings



List of abbreviations

IUCLID: International uniform chemical information database.

RTECS: Registry of Toxic Effects of Chemical Substances.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.